

## Twist drill type VA HSSE

For use in stainless steel and special alloys

**ATORN**<sup>®</sup>



### Application

For use in stainless steel, special alloys up to a strength of 1300 N/mm<sup>2</sup>.

### Version

- Twist drill with stainless steel profile

### Advantage

- special geometry with aggressive flute design and free geometry for very smooth cutting

### Delivery

Packaging unit: drill Ø 1.0-6.0 mm = 10 pieces (price per piece)

Application	Steel (N/mm <sup>2</sup> )			Stainless steel		Alu		Brass		Bronze		Plas-tics	Graphite G(C)FK	GG(G) GJMW	Titan-alloy	Nickel-alloy	Super-alloy	Hard mat.	
	<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long							<55 HRC	<65 HRC
	30	20	10	10	20	50	70	70	45	40	30				10	10	10		

<b>Art. No.</b>	<b>11029 125</b>
<b>Cutting material</b>	HSSE
<b>Surface</b>	Uncoated
<b>Type</b>	VA
<b>Angle of the tip</b>	130 Degree
<b>Tool holding device</b>	HA parallel shank
<b>Cutting edge diameter</b>	1.45 mm
<b>Chip flute length</b>	18 mm
<b>Length</b>	40 mm
<b>f stainless steel</b>	0.03 mm/U
<b>DIN</b>	338

### EAN-Code

405029342855 1