

**Einsatzwerte**

Spiralbohrer VHM Typ N 5xD ohne IK (Art.-Nr. 1003110 098,  
1011020 090-200)



| Materialgruppen für Schnittwerte       | Festigkeit [N/mm²] | Bezeichnung nach DIN | Vc [m/min] | f [mm/U] bei Durchmesser |             |           |           |            |
|--|--------------------|----------------------|------------|--------------------------|-------------|-----------|-----------|------------|
|  |                    |                      |            | 0-3                      | 3-5         | 5-8       | 8-12      | 12-16      |
| <b>1. Stähle</b>                       |                    |                      |            |                          |             |           |           |            |
| 1.1 Automatenstahl                     | < 900              | 9 S 20               | 55-75      | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 1.2 Baustahl                           | <500               | ST 37-2              | 55-75      | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 1.3 Baustahl                           | > 500              | ST 60-2              | 50-70      | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 1.4 Vergütungsstahl                    | <1000              | 42 CrMo 4            | 50-60      | 0.02-0.085               | 0.085-0.09  | 0.09-0.12 | 0.12-0.17 | 0.17-0.2   |
| 1.5 Stahlguss                          | <1000              | GS-45                | 40-60      | 0.02-0.085               | 0.085-0.09  | 0.09-0.12 | 0.12-0.17 | 0.17-0.2   |
| 1.6 Einsatzstahl                       | <1200              | 16 MnCr 5            | 45-75      | 0.02-0.085               | 0.085-0.09  | 0.09-0.12 | 0.12-0.17 | 0.17-0.2   |
| 1.7 Edelstahl ferritisch/martensitisch | <1100              | X 10 Cr 13           | 20-40      | 0.02-0.085               | 0.085-0.09  | 0.09-0.12 | 0.12-0.17 | 0.17-0.2   |
| 1.8 Vergütungsstahl                    | >1000              | 43 CrMo 4            | 45-60      | 0.02-0.075               | 0.075-0.085 | 0.085-0.1 | 0.1-0.14  | 0.14-0.17  |
| 1.9 Nitrierstahl                       | <1300              | 31 CrMoV 9           | 45-65      | 0.02-0.075               | 0.075-0.085 | 0.085-0.1 | 0.1-0.14  | 0.14-0.17  |
| 1.10 Werkzeugstahl                     | <1300              | X 38 CrMoV 5 1       | 25-40      | 0.02-0.075               | 0.075-0.085 | 0.085-0.1 | 0.1-0.14  | 0.14-0.17  |
| <b>2. Rostfreie Stähle</b>             |                    |                      |            |                          |             |           |           |            |
| 2.1 Edelstahl, austenitisch            | <1100              | G-X 2 CrNiMo 18 15   | 20-40      | 0.02-0.085               | 0.085-0.09  | 0.09-0.12 | 0.12-0.17 | 0.17-0.2   |
| <b>3. NE-Metalle</b>                   |                    |                      |            |                          |             |           |           |            |
| 3.1 Aluminium, langspanend             | <500               | Al99.9               | 150-230    | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.2 Aluminium, kurzspanend             | <500               | G-AlSi12             | 100-170    | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.3 Kupferleg. Bronze langspanend      | <1200              | CuSn4                | 80-140     | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.4 Kupferleg. Bronze kurzspanend      | <850               | CuNi12Zn24           | 80-120     | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.5 Kupferleg. Messing langspanend     | <600               | Cu Zn 20             | 100-180    | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.6 Kupferleg. Messing kurzspanend     | <600               | Cu Zn 39 Pb 3        | 100-160    | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.7 Thermoplast                        | <100               | PVC, Acrylglas       | 25-80      | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.8 Duroplast                          | <150               | Bakelit, Melamin     | 20-80      | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.9 Faserverstärkte Kunststoffe        | <1500              | CFK, GFK             | 20-60      | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.10 Graphite                          | <60                | C8000                | 60-100     | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.21 | 0.21-0.225 |
| 3.11 Verbundwerkstoffe                 |                    |                      |            |                          |             |           |           |            |
| <b>4. Guss</b>                         |                    |                      |            |                          |             |           |           |            |
| 4.1 Grauguss                           | <260 HB            | GG10                 | 60-110     | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.2  | 0.2-0.21   |
| 4.2 Sphäroguss                         | <310 HB            | GGG 40               | 60-110     | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.2  | 0.2-0.21   |
| 4.3 Gusseisen mit Kugelgraphit         | <280 HB            | GTW-55               | 60-110     | 0.02-0.085               | 0.085-0.1   | 0.1-0.15  | 0.15-0.2  | 0.2-0.21   |
| <b>5. Sonderlegierungen</b>            |                    |                      |            |                          |             |           |           |            |
| 5.1 Titanlegierung                     | <1200              | TiAl5Sn2,5           | 10-40      | 0.02-0.075               | 0.075-0.085 | 0.085-0.1 | 0.1-0.14  | 0.14-0.17  |
| 5.2 Nickelbasislegierung               | <1400              | NiCr21Mo             | 10-35      | 0.02-0.075               | 0.075-0.085 | 0.085-0.1 | 0.1-0.14  | 0.14-0.17  |
| 5.3 Superlegierungen                   | <1400              | X45CrSi 9 3          | 10-25      | 0.02-0.075               | 0.075-0.085 | 0.085-0.1 | 0.1-0.14  | 0.14-0.17  |



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com