

Roller container for LIFT workbench

For workbenches LIFT art. no. 1082251 101-106



Execution

- Housing in robust welded sheet steel construction
- Useful height of housing 360 mm (= clear internal dimension)
- 2 fixed castors, 2 swivel castors with locking device, dia. 125 mm, load per castor 200 kg
- Drawers as standard with 100 % full-extension slide, single extension lock
- Drawer internal dimensions W x D 500 x 540 mm
- Drawer load capacity 100 kg
- High-quality aluminium handle strip with labelling strips
- Central locking: DOM interchangeable cylinder
- Lock is master-key-compatible
- Powder-coated surface



Advantage

- Maximum possible load including tare weight 600 kg
- When creating locking systems, the standard locking core can simply be replaced with a locking-system-compatible locking core

Delivery

With practical deposit tray as standard (4-sided anti-roll-off edging) and non-slip mat

Notes

To order customised hard foam inserts, please use the following clear internal dimensions: W x D 490 mm x 530 mm. Specified load values always apply to evenly distributed surface loads. Other colours available on request at extra cost.

Technical Data

Product number	1082252 601
With single pull-out safety brake	Yes
Central locking	Yes
Lock type	DOM® cylinder lock
With sliding handle	Yes
Pullout type	Full extension
Drawer width (inner dimension)	500 mm
Number of fixed rollers	2 PCS
Drawer depth (inner dimension)	540 mm
Number of steering rollers	2 PCS
Load-carrying capacity per drawer	100 kg
Number of loading surfaces	1 PCS
Number of wheel adjusters	2 PCS
Material of wheel	TPE
Wheel diameter	125 mm
Material	Sheet steel
Surface	Powder-coated
Manufacturer Part Number	999.101.0028
Commodity Code	94032080



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com