

Wall-mounted cabinet Smooth or perforated back panel



Execution

- Doors made of solid sheet metal or with viewing window made from shatterproof acrylic glass
- The pane impact strength of 15 kJ/m² corresponds to a force of approx. 1500 kg/m² from a height of 1 m
- Doors with reinforcement pocket and cylinder lock with 2 keys
- With holes for wall mounting
- With a powder-coated shelf in body colour, height-adjustable on 17 mm grid
- Shelf load capacity of 15 kg with evenly distributed load
- Overall load capacity per cabinet 30 kg with evenly distributed load
- TÜV/GS approved

Notes

For additional shelves, see art. no. 1084847 112-213.



Technical Data

| | |
|----------------------------------|----------------------|
| Product number | 1084847 103 |
| Back panel design | Smooth |
| Number of shelves | 1 PCS |
| Load-carrying capacity per shelf | 15 kg |
| Central locking | Yes |
| Lock type | Cylinder lock |
| Load-carrying capacity | 30 kg |
| Material | Sheet steel |
| Surface | Powder-coated |
| Manufacturer Part Number | 22337-080-001-735512 |
| EAN Code | 4024496123810 |
| Commodity Code | 94032080 |



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com