

Wall-mounted cabinet Smooth or perforated back panel



Execution

- Doors made of solid sheet metal or with viewing window made from shatterproof acrylic glass
- The pane impact strength of 15 kJ/m² corresponds to a force of approx. 1500 kg/m² from a height of 1 m
- Doors with reinforcement pocket and cylinder lock with 2 keys
- With holes for wall mounting
- With a powder-coated shelf in body colour, height-adjustable on 17 mm grid
- Shelf load capacity of 15 kg with evenly distributed load
- Overall load capacity per cabinet 30 kg with evenly distributed load
- TÜV/GS approved

Notes

For additional shelves, see art. no. 1084847 112-213.



Technical Data

Product number	1084847 202
Back panel design	Perforated
Number of shelves	1 PCS
Load-carrying capacity per shelf	15 kg
Central locking	Yes
Lock type	Cylinder lock
Load-carrying capacity	30 kg
Material	Sheet steel
Surface	Powder-coated
Manufacturer Part Number	22337-040-101-735716
EAN Code	4024496123940
Commodity Code	94032080



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com