

### Wall-mounted cabinet Smooth or perforated back panel



#### Execution

- Doors made of solid sheet metal or with viewing window made from shatterproof acrylic glass
- The pane impact strength of 15 kJ/m<sup>2</sup> corresponds to a force of approx. 1500 kg/m<sup>2</sup> from a height of 1 m
- Doors with reinforcement pocket and cylinder lock with 2 keys
- With holes for wall mounting
- With a powder-coated shelf in body colour, height-adjustable on 17 mm grid
- Shelf load capacity of 15 kg with evenly distributed load
- Overall load capacity per cabinet 30 kg with evenly distributed load
- TÜV/GS approved

#### Notes

For additional shelves, see art. no. 1084847 112-213.



### Technical Data

|                                  |                    |
|----------------------------------|--------------------|
| Product number                   | <b>1084847 101</b> |
| Back panel design                | Smooth             |
| Number of shelves                | 1 PCS              |
| Load-carrying capacity per shelf | 15 kg              |
| Central locking                  | Yes                |
| Lock type                        | Cylinder lock      |
| Load-carrying capacity           | 30 kg              |
| Material                         | Sheet steel        |
| Surface                          | Powder-coated      |
| Manufacturer Part Number         | 22337-040-001-735  |
| EAN Code                         | 4024496123797      |
| Commodity Code                   | 94032080           |



**Hommel Hercules Werkzeughandel GmbH & Co. KG**

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | [info@hommel-hercules.com](mailto:info@hommel-hercules.com)