

PRODUCT DATA SHEET

Wall-mounted cabinet

Smooth or perforated back panel



Execution

- Doors made of solid sheet metal or with viewing window made from shatterproof acrylic glass
- The pane impact strength of 15 kJ/m2 corresponds to a force of approx. 1500 kg/m2 from a height of 1 m
 Doors with reinforcement pocket and cylinder lock with 2 keys

- Doors with reinforcement pocket and cymrocrited and cymrocrited and cymrocrited and cymrocrited and cymrocrited and construct and cymrocrited and construct and construct and construct and construct and construct and cymrocrited and cymrocrited and cymrocrited and construct and cymrocrited and cym
- Overall load capacity per cabinet 30 kg with evenly distributed load TÜV/GS approved

Notes

For additional shelves, see art. no. 1084847 112-213.

Technical Data

| Product number | 1084847 207 |
|----------------------------------|-------------------|
| Back panel design | Perforated |
| Number of shelves | 1 PCS |
| Load-carrying capacity per shelf | 15 kg |
| Central locking | Yes |
| Lock type | Cylinder lock |
| Load-carrying capacity | 30 kg |
| Material | Sheet steel |
| Surface | Powder-coated |
| | |
| Manufacturer Part Number | 22337-040-191-735 |
| EAN Code | 4024496123995 |
| Commodity Code | 94032080 |



