

### ER collet chuck

In accordance with DIN 2080

G 6,3 15000 1/min	DIN 2080
-------------------------	-------------

**ATORN**

#### Application

For clamping tools with straight shank in ER collet chucks in accordance with DIN 6499.

#### Execution

- Alloyed case-hardening steel, core tensile strength at least 950 N/mm<sup>2</sup>.
- Internal coolant supply.
- Case-hardened HRC 60 ± 2 (HV 700 ± 50), hardening depth 0.8 mm ± 0.2 mm.
- Max. concentricity < 0.005 mm.
- Taper angle tolerance quality < AT3 in accordance with DIN 7187 and DIN 2080.
- With Balluff chip hole.
- All functional surfaces machined.
- All ER16 collet chucks feature a hexagon nut.

#### Delivery

1x ER collet chuck SK30, SK40 or SK50 (DIN2080).



### Technical Data

Product number	<b>1021511 115</b>
Tool holding device	SK 50
Collet type	ER 40
Min./max. clamping range	3-26 mm
Projecting length	63 mm
Outer diameter	63 mm
Manufacturer Part Number	22661279
EAN Code	4050293714968
Commodity Code	84661020



**Hommel Hercules Werkzeughandel GmbH & Co. KG**

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com