

Shrink-fit chuck 3°

In accordance with ISO 7388-2 (JIS B6339/MAS-BT); long and slim version



ATORN

Application

For clamping cutters and drills with straight shanks in h6 tolerance. Suitable for heavy-duty machining and all high-power applications. Suitable for inductive, contact and hot air shrinking devices.



Execution

- Guaranteed maximum concentricity 0.003 mm.
- Shrink fit and shrink release of carbide and HSS tools.
- Hardness 52 + 2 HRC.
- Maximum coolant pressure 80 bar.
- Glass bead blasted.

Advantage

- Slim design, extremely low interference contour.
- High transmittable torques.
- High positioning and repeat accuracy.
- Ideal for high rotation speeds.

Delivery

1x shrink-fit chuck 3° BT40 (ISO 7388-2).

Notes

The previous standard JIS B 6339 MAS BT was replaced by ISO 7388-2.

Technical Data

Product number	1021653 124
Tool holding device	BT 40
Clamping diameter	5 mm
Tapered diameter	11 mm
Projecting length	160 mm
Outer diameter	21 mm
Manufacturer Part Number	21044865
Commodity Code	84661038



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com