


Automatic welding filter 3M™ Speedglas™ 9100X



Application

Electrode welding, micro-plasma welding, TIG welding, MIG/MAG welding and autogenous welding/cutting.

Execution

3M™ Speedglas™ 9100X automatic welding filter, protection level 5, 8, 9-13 variable with a large field of view. The comfort mode for tack welding protects the eyes from fatigue. The delay function allows the brightening delay to be adjusted as desired. Switching time light-dark 0.1 ms (+23 °C), brightening time dark-light adjustable 40-1,300 ms. Light level 3. Viewing window size 54 x 107 mm. Battery life of up to 2,500 hours and additional solar cells. Approved in accordance with EN 379, EN 166.

Notes

Suitable for 3M™ Speedglas™ 9100 welding mask.



Technical Data

Product number	1093009 653
EN standard	379 166
UV and IR protection	Protection level 13 (permanent)
Translucency when activated	Protection level 5 Protection level 8 Protection level 9-13
Translucency when not activated	Protection level 3
Energy supply	Solar cells and 2 replaceable 3 V button cells (CR2032)
Manufacturer Part Number	7000000221
EAN Code	4046719188406
Commodity Code	85241100



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com