


Welding mask 3M™ Speedglas™ 9100 V



Application

Electrode welding, micro-plasma welding, TIG welding, MIG/MAG welding and autogenous welding/cutting.

Execution

3M™ Speedglas™ welding mask 9100 complete with 3M™ Speedglas™ 9100V automatic welding filter, blackness value 5, 8 and 9-13 variable. Lightweight, shock-resistant and radiation-resistant mask shell with even greater protection thanks to heat-reflective front cover. Side windows for improved all-round visibility. Exhalation system to prevent high CO₂ concentrations while keeping the mask mist-free. The newly developed headband with four locking stages and two adjustable cross straps ensure maximum comfort. An easy to turn knob on the back of the head enables precise adjustment of the mask. Viewing window size 45 x 93 mm. Battery life 2,800 hours, with additional solar cells. Meets EN 379, EN 175.



Technical Data

Product number	1093009 650
EN standard	379 175 166
UV and IR protection	Protection level 13 (permanent)
Translucency when activated	Protection level 5 Protection level 8 Protection level 9-13
Translucency when not activated	Protection level 3
Energy supply	Solar cells and 2 replaceable 3 V button cells (CR2032)
Manufacturer Part Number	7000000217
EAN Code	4046719186815
Commodity Code	65061010



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com