


Automatic welding filter 3M™ Speedglas™ 100 V



Application

The anti-glare technology is suitable for most types of arc welding process, including shielded metal arc, MIG/MAG and TIG welding.

Execution

3M™ Speedglas™ 100 V automatic welding filter with five selectable blackness values 8-12. It also offers three sensitivity levels for optimum adaptation to different welding conditions. The delay function allows the brightening delay to be adjusted as desired. Switching time light-dark 0.1 ms (+23 °C), brightening time dark-light 40-250 ms. Light level 3. Viewing window size 44 x 93 mm. Battery life of up to 1,500 hours. Tested in accordance with EN 379, EN 175B.

Notes

Suitable for 3M™ Speedglas™ 100 welding mask.



Technical Data

| | |
|---------------------------------|---|
| Product number | 1093009 628 |
| EN standard | 379 166 169 |
| UV and IR protection | Protection level 12 (permanent) |
| Translucency when activated | Protection level 8-12 |
| Translucency when not activated | Protection level 3 |
| Energy supply | 2 replaceable 3 V button cells (CR2032) |
| Manufacturer Part Number | 7100167242 |
| EAN Code | 4046719712922 |
| Commodity Code | 85241100 |



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com