

PRODUCT DATA SHEET

Cable drum

Sheet steel drum



Application

Approved for continuous use outdoors.

Execution

- Drum made of zinc-plated sheet steel
- Earthed drum
- Stable cable reel with sturdy tubular steel frame
- Ergonomic, insulated bow handle
- Plug parking station
- Rotation stop switch
- Extremely stable due to low centre of gravity
- Splash-proof 3-way outlet with plug sealing lip
- Thermal protection switch in accordance with VDE 0620 and Diag S

- Advantage Rapid fault diagnostics using the new cable drum diagnostics system (Diag S):
- Green light on: Power supply is active. The cable drum is ready for operation. If the connected device does not work, there is an error with the connected cable or the device itself.
- Red light on: Connected, powered devices are not working as the thermal protection switch has been triggered. As soon as the cable drum has cooled down and the thermal protection switch is pressed, the cable drum can be used again.
- Both lights off: The cable drum is not receiving power. It is not plugged in or the connecting outlet has no power. The cable drum is defective. A specialist should be consulted for repairs.

Notes

Complies with BGI 600, K1.

Technical Data

Product number	1088205 202
Material of drum body	Steel plate
Diameter	255 mm
Colour of cable	Black
Width x height x depth	258 x 358 x 240 mm
IP protection class	IP 44
Manufacturer Part Number	K1S40NTF
EAN Code	4024496129102
Commodity Code	85444290



