

Cable drum Plastic drum

IP
44

Application

Approved for continuous use outdoors as well as on construction and installation sites.

Execution

- Plastic drum
- Stable cable reel with sturdy tubular steel frame
- Ergonomic, insulated bow handle
- Plug parking station
- Rotation stop switch
- Extremely stable due to low centre of gravity
- Splash-proof 3-way outlet with plug sealing lip
- Thermal protection switch in accordance with VDE 0620 and Diag S

Advantage

- Rapid fault diagnostics using the new cable drum diagnostics system (Diag S):
- Green light on: Power supply is active. The cable drum is ready for operation. If the connected device does not work, there is an error with the connected cable or the device itself.
- Red light on: Connected, powered devices are not working as the thermal protection switch has been triggered. As soon as the cable drum has cooled down and the thermal protection switch is pressed, the cable drum can be used again.
- Both lights off: The cable drum is not receiving power. It is not plugged in or the connecting outlet has no power. The cable drum is defective. A specialist should be consulted for repairs.

Notes

Complies with German professional association regulations BGI 608 and BGI 600, K2.



Technical Data

Product number	1088206 202
Material of drum body	Plastic
Diameter	255 mm
Colour of cable	Black
Width x height x depth	258 x 358 x 240 mm
IP protection class	IP 44
Manufacturer Part Number	K1Y40NTF
EAN Code	4024496129119
Commodity Code	85444290



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com