

PRODUCT DATA SHEET

Electro-mechanical blind rivet setting tool FireBird® Pro CAS



Application

For processing M3-M10 rivet nuts.

Execution

- With automatic setting and untwisting function
- Controlled by the setting force
 Cordless, for 18 V/2.0 Ah CAS Li-ion sliding battery

- Compatible with the Contabo CAS battery system
 Quick and easy setting force adjustment via the display
 Fully automatic untwisting process
- No wear thanks to BLDC motor

Delivery

1 18 V/2.0 Ah CAS rechargeable battery (Li-ion)

1 charger for 18 V Li-ion CAS rechargeable batteries

Thread mandrel and M6 nosepiece (in working position)

Thread mandrel and M4 and M5 nosepiece (accessories)

1 hex socket wrench

2 double open-end wrenches AF 24/27 mm

Quick setting instructions

Setting force pre-adjustment card

Operating instructions

Supplied in L-BOXX

Technical Data

| Product number | 1054860 202 |
|--|------------------|
| Battery voltage | 18 V |
| Rechargeable battery/battery capacity | 2 Ah |
| Type of rechargeable battery/battery | Li-lon |
| Number of rechargeable batteries/batteries | 1 PCS |
| Motor design | Brushless motor |
| | |
| Manufacturer Part Number | FIREBIRD PRO CAS |
| EAN Code | 4007081102513 |
| Commodity Code | 84672920 |
| | |

