



### Execution

- Universal one-handed quick-action coupling with single-sided locking at an extremely attractive price.
- The closed locking sleeve prevents contamination of internal parts.
- When using steel nipples, this coupling can also be used on pneumatic tools due to its hardened locking pins.
- Couplings and nipples with sealing thread coating
- Ready-to-fit polyacrylate thread coating for instant and high-level sealing without curing. The permanently elastic sealing material can be readjusted up to 45° without affecting the seal. Safe for health. Easy assembly and disassembly.
- To avoid injuries or whipping, we recommend holding the plug-in nipple firmly with one hand when uncoupling.

### Notes

This quick-action coupling is not suitable for direct mounting on pulsating tools.



## Technical Data

|                          |             |
|--------------------------|-------------|
| Product number           | 1075119 207 |
| Type                     | 243.49-E    |
| DN nominal width         | DN 7,2      |
| Connection               | LW 10       |
| Max. operating pressure  | 35 bar      |
| Min. operating pressure  | 0 bar       |
| Length                   | 54 mm       |
| Manufacturer Part Number | 115653      |
| Commodity Code           | 84812090    |



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com