



### Execution

- Universal one-handed quick-action coupling with single-sided locking at an extremely attractive price.
- The closed locking sleeve prevents contamination of internal parts.
- When using steel nipples, this coupling can also be used on pneumatic tools due to its hardened locking pins.
- Couplings and nipples with sealing thread coating
- Ready-to-fit polyacrylate thread coating for instant and high-level sealing without curing. The permanently elastic sealing material can be readjusted up to 45° without affecting the seal. Safe for health. Easy assembly and disassembly.
- To avoid injuries or whipping, we recommend holding the plug-in nipple firmly with one hand when uncoupling.

### Notes

This quick-action coupling is not suitable for direct mounting on pulsating tools.



## Technical Data

Product number	<b>1075119 210</b>
Type	243.22-E
Connection thread	IT 3/8 inch
DN nominal width	DN 7,2
Max. operating pressure	35 bar
Min. operating pressure	0 bar
Length	40.5 mm
Width across flats	21 mm
Manufacturer Part Number	115632
Commodity Code	84812090



**Hommel Hercules Werkzeughandel GmbH & Co. KG**

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | [info@hommel-hercules.com](mailto:info@hommel-hercules.com)