

Digital manifold with Bluetooth

IP
54



Application

The testo 550i app-controlled digital manifold with Bluetooth®, two-way valve block and robust hook offers extensive measurement technology in an extremely compact package. This extremely robust manifold allows you to wirelessly, easily and reliably carry out your daily work on refrigeration and air conditioning systems and heat pumps. All using the testo Smart app on your smartphone or tablet.

Execution

- All tasks from measurement to documentation using the testo Smart app on your smartphone. For rapid, easy measurements on refrigeration and air conditioning systems and heat pumps.
- Maximum reliability and convenient use in hard-to-reach places thanks to particularly compact, extremely robust housing with protection class IP54
- Pressure testing:
 - Measuring range: -1 to 60 bar
 - Accuracy: $\pm 0.5\%$ FS
 - Resolution: 0.01 bar
 - Refrigerants in the instrument
- R407H; R23; R290; R1234yf; R442A; R134a; R123; R452B; R438A; R421A; R453a; R401B; R1233zd; R410A; R407A; R407C; R452A; R401A; R422C; R427A; R422B; R424A; R125; R414B; R404A; R408A; R448A; R422D; R12; R114; R421B; R449A; R409A; R420A; R444B; R32; R454A; R124; R402A; R450A; R407F; R416A; R13; R437A; R1234ze; R454B; R402B; R22; R434A; R454C; R455A; R458A; R500; R502; R503; R507; R513A; R600a; R718 (H₂O); R744 (CO₂)
- Refrigerants updatable via app
- R11; FX80; I12A; R1150; R1270; R13B1; R14; R142B; R152A; R161; R170; R227; R236fa; R245fa; R401C; R406A; R407B; R407D; R41; R411A; R412A; R413A; R417A; R417B; R417C; R422A; R426A; R508A; R508B; R600; RIS89; SP22
- testo Smart app: Control all service and maintenance work via app and smartphone or tablet, clearly displayed results, digital documentation, set favourites, always have the latest refrigerants at your fingertips
- Can be expanded with the testo smart probes for temperature, humidity and vacuums

Advantage

- The smallest digital manifold on the market

Delivery

- 1x testo 550i digital two-way manifold
- 3x AAA batteries
- 1x calibration log
- 1x operating instructions



Technical Data

Product number	1033965 315
Length	77 mm
Width	109 mm
Height	63 mm
IP protection class	IP 54
Manufacturer Part Number	0564 2550
Commodity Code	90262020



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com