


### Synchro screw tap, HSSE-PM TiN M ISO 2 (6H) 0° 376 B

For universal use up to 1000 N/mm<sup>2</sup>



**ATORN**

#### Application

For producing metric threads on CNC machines or conventional machines in **through holes** in the steel, stainless steel, non-ferrous metals, cast iron and special alloys material groups up to a strength of 1000 N/mm<sup>2</sup>.



#### Execution

- Dimensions pursuant to: DIN 371 = reinforced shank (up to M10), DIN 376 = transition-fit shank (from M12)

#### Advantage

- Long service life and high level of process reliability thanks to innovative cutting geometry and coating, and universal application for maximum flexibility in use
- Individual clamping options: Shrink-fit chuck, synchro tapping chuck
- Precise shank design: h6

### Technical Data

Product number	<b>1003140 333</b>
Thread type x nominal diameter	M12
Pitch	1.75 mm
Core hole diameter	10.2 mm
Length	110 mm
Shank diameter	9 mm
Shank square	7 mm
DIN	376
EAN Code	4050293579079
Commodity Code	82074010



**Hommel Hercules Werkzeughandel GmbH & Co. KG**

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com