

### Screw tap, HSSE UNF 2B 40° (right) 376 similar to C

For universal use up to 1000 N/mm<sup>2</sup>



**ATORN**

#### Application

For producing UNF (Unified Fine) threads on CNC machines or conventional machines in **blind holes** in the steel, (stainless steel), non-ferrous metals and (cast iron) material groups up to a strength of 1000 N/mm<sup>2</sup>.



#### Execution

- With protruding shank

#### Advantage

- Innovative cutting geometry for very high dimensional accuracy, process reliability and chip removal.
- High-quality, torsion-resistant HSSE cutting material and cutting edge finish for very high service life requirements.
- Universal use for maximum flexibility in use.

## Technical Data

Product number	<b>1014575 207</b>
Thread type x nominal diameter in inches	UNF 1/2 in
Number of thread starts per inch	20
Core hole diameter	11.5 mm
Length	100 mm
Shank diameter	9.0 mm
Shank square	7.0 mm
DIN	Similar to 376
Manufacturer Part Number	10471040
EAN Code	4050293020632
Commodity Code	82074010



**Hommel Hercules Werkzeughandel GmbH & Co. KG**

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com