

### Screw tap, HSSE G ISO 2 (6H) 40° (right) 374 C for universal use up to 1000 N/mm<sup>2</sup>



**ATORN**

#### Application

For producing pipe threads on CNC machines or conventional machines in blind holes in the steel, stainless steel, non-ferrous metals and cast material groups up to a strength of 1000 N/mm<sup>2</sup>.

#### Execution

- With protruding shank

#### Advantage

- Universal use for maximum flexibility of application
- Innovative cutter geometry ensures high process reliability even in difficult machining conditions



### Technical Data

|  |                    |
|--|--------------------|
| Product number                           | <b>1003141 435</b> |
| Thread type x nominal diameter in inches | G 3/8 in           |
| Number of thread starts per inch         | 19                 |
| Core hole diameter                       | 15.3 mm            |
| Length                                   | 100 mm             |
| Shank diameter                           | 12 mm              |
| Shank square                             | 9 mm               |
| DIN                                      | 374                |
| Manufacturer Part Number                 | 11290961           |
| EAN Code                                 | 4050293423617      |
| Commodity Code                           | 82074010           |



**Hommel Hercules Werkzeughandel GmbH & Co. KG**

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com