


Screw tap, HSSE-PM Ultra HL uniform shank H6 M ISO 2X (6HX) 0° 371 B for universal use up to 1000 N/mm²



ATORN

Application

For producing metric threads on CNC machines or conventional machines in **through holes** in steel, stainless steel, non-ferrous metals, cast iron and special alloys up to 1200 N/mm².



Advantage

- Ideal for long service life requirements and materials that are difficult to machine, such as stainless steel
- Innovative cutting geometry and ULTRA HL coating guarantee high process reliability even under difficult machining conditions
- h6 uniform shank for clamping in shrink-fit chucks
- HSSE PM cutting material for longer service life

Technical Data

| | |
|--------------------------------|--------------------|
| Product number | 1003140 253 |
| Thread type x nominal diameter | M3 |
| Pitch | 0.5 mm |
| Core hole diameter | 2.5 mm |
| Length | 56.00 mm |
| Shank diameter | 6.00 mm |
| Shank square | 4.90 mm |
| DIN | 371 |
| EAN Code | 4050293650563 |
| Commodity Code | 82074010 |



Hommel Hercules Werkzeughandel GmbH & Co. KG

Heidelberger Str. 52 | 68519 Viernheim | +49 (0) 6204 739-0 | info@hommel-hercules.com