

PRODUCT DATA SHEET

High-performance reamer, solid carbide TiALN

With cast steel geometry for use up to 1300 N/mm²























Application

for cutting fit tolerances in blind holes on modern CNC machines with steady tool and workpiece clamping up to 1300 N/ $\,\mathrm{mm^2}$.

Execution

■ Straight grooved with extremely variable pitch and internal cooling, **type A**

Advantage

- innovative cutting geometry ensures excellent dimensional accuracy and process reliability for very high cutting parameters
- high-quality solid carbide cutting material and coating ensure a very long service life
- Internal cooling ensures optimum chip removal

Notos

Make sure that tools are accurately and tightly clamped (ideally use a hydro-mechanical clamping chuck or precision collet chuck). Note: Please refer to dimension table.

Technical Data

| Product number | 1013522 257 |
|--------------------------|---------------|
| Cutting edge diameter | 16 mm |
| Tolerance of fit | H7 |
| Length | 150 mm |
| Cutting edge length | 25 mm |
| Projecting length | 100 mm |
| Shank diameter | 16 mm |
| Number of cutting edges | 6 PCS |
| f steel 1300 | 0.8 mm/r |
| | |
| Manufacturer Part Number | 12160205 |
| EAN Code | 4050293395440 |
| Commodity Code | 82076030 |
| | |

